## coverguard



www.coverguard-safety.com

420 rue de la Dombes

01700, MIRIBEL, France



HAND

#### **EUROSTRONG M0154**

- Docker glove in split cowhide leather • Green split leather reinforcement on the
- palm, index and thumb Cotton lined palm



2240

#### **EUROSTRONG M02240**

- Master glove in soft full grain goat leather • Elastic wrist thightening
- Wing thumb
- Ocomfort, flexibility and extended



#### **MO2410 EUROSTRONG**

- O Driver glove in beige full grain cowhide
- $\ensuremath{\bullet}$  Wing thumb, and elastic wrist band at the back of the





EN ISO 20345

 $\epsilon$ 

• Heel and toe Stark® scuff caps



**PYROPE** 

# **PUROFORT®+ RELIANCE**



O Purofort® upper, reflective trim at the top • Purofort® / Vibram® XS Work outsole

**⊕** 50 % lighter

• Excellent grip in greasy environment











- Monted grey seamless support from
   HPPE, mineral fibre, polyamide, elastane
   Double coating 3/4 hand in smooth blue nitrile and black sandy nitrile finishing.
- on the palm Oil and grease proof ♠ Excellent grip in oil
- Reduces muscle fatigue and improves productivity







#### **EUROCUT IMPACT 200**

- Grey seamless knit from HDPE, polyester and elastane O Double soft nitrile coating on the 3/4 hand and full
- Black sandy nitrile en the palm
- O TPR reinforcements on the back of the hand and fingers



◆ Acifort® upper

• Steel toe cap



• Durable shaft and tear resistance

9LAH052

• Full grain leather upper

• Good resistance to hydrolysis

Steel toe cap • Nitrile rubber outsole EN ISO 20345

• Full grain leather upper Steel toe cap

• Nitrile rubber sole, resistant to heat and • Defined heel for better safety espe





HRO

• Full leather upper • Reinforcement : front in PU and back in TPU

● Reflective trim at the back





**EUROLITE 15N505** 

3/4 double palm nitrile coating

• Second skin sensation and increased skin

OEKO-TEX

Excellent comfort and exceptional grip in oily areas

protection against dermatitis risks

- Cotton support • Red PVC full coating Treated with Actifresh
- O Length: 36 cm







C € EUROCHEM M05540 Green acrylonitrile, thickness: 0.56mm

> Durable chemical protection Grip, comfort, absorption of perspiration

O Long straight cuff: length 45cm





#### **EUROCHEM M03740**

- Green PVC full coating
- O Double coating on hand with "sandy" finish • Safety scalloped cuff: length 40cm

Actifresh treatment for imporved hygiene









- Increased hearing protection • PU foam without latex
- Reusable and washable
- Cord (allows to keep earplugs around the neck when not used)



**MAX200** 



- Red ABS cups +Black adjustable headband Soft PVC cushions leather touch
- Increased hearing protection SNR 26,7dB

EN 352-2:2002



O High hearing protection (30dB)
O Very good combination of high protection and lightness

• Adjustable on all safety helmets with pre-cut slits













Welding



IEC61482-2 EN ISO 14404 CLASS 1-4 11611 TYPE 2



O Plastic trims, O&G industries, Electrical, automative and





side venting

**CLASSIC** 

• Available in red, yellow, green, orange, blue

 $\epsilon$ M065300 CE • Polypropylene shell 6ALB200 6 points nylon web harness • HDPE shell in high density polyethylene • Ratchet adjustment from 55 to 62 cm O Dielectric protection 1000AV / 1500VDC - Classe 0 / Sweatband of 37 cm • 6 points nylon web harness • Adjusment with rachet from 53 to 62 cm

• Fits with earmuffs

EN 50365

**PACIFIC** 

**7PERS10** 

PERSONAL FALL LIMITER 2M EDGE



O Panoramic vision

- Fits over prescription glasses
- Flexible and self-adjustable temples
- O Upper and side protection
- Hard coated, anti-scratch and anti-UV





60VEC00NSI

- Polycarbonate lense, polycarbonate/TPE/nylon
- Overspectacles suitable with prescription glasses • Panoramic lens with integrated side protection

**ETNA** 

• Adjustable temples graduate to soft material for









Flasticated waist wrists ankles

EN ISO 13688:2013



EN 13982 EN 14116

TYPF 5




**COVERPRO 4M42** 

O Microporous coverall 65g/m², hood, white Waterproof against spray mists • Central zip under adhesive flap Taped and stitched seams

2002 TYPE 4 TYPE 5 2003





**HYDRA** 

**COVERCHEM 3X60** 

2002

EN 1149-5 EN 13982 EN 1073 TYPE 3

EN 13034 EN 13982 TYPE 4 **®** 

EN 13982 EN 14126 TYPE 5 2003





• Shoulder and leg straps of different colours

• Self Retracting Lifeline webbing 2m **◆** EDGE certification for use on sharp edge • Fall factor 2, can be connected at foot level

 $\epsilon$ 









#### FFP 3 NR 23316

O Half mask in polypropylene and polyester with valve and PU nose seal (latex free)

• Preformed design: fits with glasses or goggles to Strength, stability and resistance O Specific design of the exhalation valve reduce

breathing resistance and avoid fog and heat inside FN 149 : 2001+A1:2009 0% METAL



6ETN200 TPE half mask with 2 filters (not included) • 4 point head harness and exhalation valve to avoid fog and heat inside the mask

• Adaptable on any face shape and comfortable • Good balance on the face : 2 filters





● 180°C field of view, distortion free

• Reinforced seal by automatic locking buckles, with 5 adjustable straps of high quality rubber



EN 20471 CLASS 2

**C** € 70242 / 70252 • Waistcoat mesh 100% polyester 120g/m²

Closing by velcro • Sewn reflective bands of 5cm: 2 staps, 2 belts







O Bird's eye knit: 55% cotton/45% polyester • Comfort: cotton against the skin, segmented

• Breathability: good ventilation thanks to mesh Extended service life (anti-fouling panels, clean-liness tape)

EN 20471
CLASS 2



#### 7HYDO / 7HYDY

• Hydra rainsuit 100% polyester Oxford 300D • High waterprofness: 3000mm

• Taped seams, high colar & adjustable waistband • Comfort and breathability with mesh lining Underam ventilation







### COVERGUARD: Tel: +33 (0)4 72 26 59 60 - 420 rue de la Dombes 01700, MIRIBEL, France

molten metal

EN 55015

EN 61547

GAN60712: Protective screen against liquid

emission, electric arcs and flames, spilling