

Ref. **9GAL130**

Indoor and dry environments

Low

Low shoes



The +

Very Lightweight (430 g for size 42)
Flexibility and cushioning
Breathability

PURCHASE PACKAGING

Ref.	Size	Carton
9GAL130036	36	6
9GAL130037	37	6
9GAL130038	38	6
9GAL130039	39	6
9GAL130040	40	6
9GAL130041	41	6
9GAL130042	42	6
9GAL130043	43	6
9GAL130044	44	6
9GAL130045	45	6
9GAL130046	46	6
9GAL130047	47	6
9GAL130048	48	6

Some sizes may only be available in certain countries

See also

DESCRIPTION

The GALAXITE ESD HRO sneaker is very lightweight, flexible, and breathable: at the forefront of comfort.

Its EVA and nitrile rubber sole ensures excellent cushioning, high durability, and grip.

Metal-free, this shoe is equipped with a composite toe cap and a puncture resistant textile sole that provide optimal protection while ensuring good flexibility.

GALAXITE is an ideal shoe for work environments such as logistics, construction finishing, or DIY.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

VARIANTS



9GAL120

TECHNICAL FEATURES

Color	Black	Insole	perforated, removable EVA
Color 2	Red	Reinforcement material	TPU
Weight	430 g	Reinforcement location	Front
Upper	Mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can only comply with their Protection features if they fit perfectly and are well maintained. Before any use, perform a visual inspection to ensure they are in perfect condition and proceed with a fitting. It is advisable to choose the model that best meets the specific requirements of your workplace.

Storage instructions

Store the shoes in a dry, clean, and well-ventilated area. A storage duration exceeding 3 years is not recommended.

Washing instructions

Clean the shoes regularly using brushes, cloths, etc.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0808

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

HRO

Heat contact resistant outsole (60 seconds at 300°C)

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

COVERPERF - Breathability



COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S1PS

Safety shoes

S1PS Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance

MAJ 13/01/2026