

Ref. **9GARL70**

Multipurpose

Low

Low shoes



The +

- * Padded collar and bellows tongue for snug fit.
- * Heel scuff cap.
- * Shock absorbing EVA midsole.

PURCHASE PACKAGING

Ref.	Size	Carton
9GARL70037	37	6
9GARL70038	38	6
9GARL70039	39	6
9GARL70040	40	6
9GARL70041	41	6
9GARL70042	42	6
9GARL70043	43	6
9GARL70044	44	6
9GARL70045	45	6
9GARL70046	46	6
9GARL70047	47	6

Some sizes may only be available in certain countries



DESCRIPTION

GARNET is a leather safety shoe. The back of the model is equipped with a reinforcement to increase the protection and durability of the shoe. This model has a composite toe cap and a textile anti-perforation sole to make it a completely non-magnetic model. It is also equipped with a sole that is resistant up to 300°C on contact (for 1 minute).
Note: GARNET 9GARL70 replaces the ALTAITE 9ALTL model.

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

- Builder,
- Slater,
- Ramp agent,
- Luggage handler,
- Site supervisor,
- Docker, ...

TECHNICAL FEATURES

Weight	510 g	Outsole	Rubber nitrile
Color	Brown	Insole	Removable, textile and foam
Color 2	Red	Main assembly	Cemented
Upper	Rectified leather and polyurethane coating	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/02/22/0213 EXT 01/02/22

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)