

Ref. **9IOLL10**

Specialties

Low

Low shoes



S3



### The +

- \*PU/PU outsole: impact cushioning. Protects the back and joints.
- \*Outsole with numerous notches: easy flexing and comfort when walking.
- \*Grooves for liquid dispersment: reduces slipping.
- \*Discreet feminine look.

### PURCHASE PACKAGING

Ref.	Size	Carton
9IOLL10036	36	6
9IOLL10037	37	6
9IOLL10038	38	6
9IOLL10039	39	6
9IOLL10040	40	6
9IOLL10041	41	6

*Some sizes may only be available in certain countries*

*See also*

### VARIANTS



9IOLLH10

### DESCRIPTION

Feminine and discreet, the IOLITE shoe is a comfortable model that matches a lifestyle that is always on the move.

The burnt-effect suede leather goes perfectly with the copper color.

In order to promote flexibility and lightness, the protective toe cap and the anti-perforation sole of the shoe are made respectively of composite material and textile.

Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. IOLITE is the ideal safety shoe for the modern woman.

### SECTORS

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

## TECHNICAL FEATURES

Color	Black	Insole	HI-POLY foam
Color 2	Copper	Main assembly	Injected
Weight	464 g	Closing	Lacing closure
Upper	Suede leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/21/1366

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol