

Ref. **9JOGU80**

Synthetic Boots

PVC

Boots



S5



The +

- * SRC sole with wear indicator
- * Comfort insole that ensures all-day comfort
- * Advanced fit with innovative Snug-fit that eliminates heel slippage and heel slip and foot fatigue

PURCHASE PACKAGING

Ref.	Size	Carton
9JOGU80037	37	6
9JOGU80038	38	6
9JOGU80039	39	6
9JOGU80040	40	6
9JOGU80041	41	6
9JOGU80042	42	6
9JOGU80043	43	6
9JOGU80044	44	6
9JOGU80045	45	6
9JOGU80046	46	6
9JOGU80047	47	5
9JOGU80048	48	5
9JOGU80049	49	5

Some sizes may only be available in certain countries



DESCRIPTION

JobGUARD is a waterproof safety boot.
 SRC rated outsole for maximum grip on the toughest surfaces
 Advanced fit with Dunlop's innovative Snug-fit that eliminates heel slippage and foot fatigue
 Dunlop Comfort insole for all-day comfort.

SECTORS

Farming, silviculture and fishing

Regional/public authorities

Infrastructure, building industry

APPLICATIONS

Farming

TECHNICAL FEATURES

Color	Green	Defined heel
Weight	1200 g	
Upper	Acifort®	
Toecap	Steel	
Puncture resistant sole	Steel	
Outsole	Acifort®	
Main assembly	Cemented	
Lining	Polyester	

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **839**

Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way Kettering- Northamptonshire- NN16 8SD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol