

Ref. **9HAZG80**

Synthetic Boots

PVC

Boots



S5



The +

- * PVC compound reinforced with nitrile and polymer for a professional protection against chemical products (EN13832-3:2006).
- * Reinforced protection of the ankle.
- * Excellent grip.
- * Energy absorption in the heel area.

PURCHASE PACKAGING

Ref.	Size	Carton
9HAZG80039	39	6
9HAZG80040	40	6
9HAZG80041	41	6
9HAZG80042	42	6
9HAZG80043	43	6
9HAZG80044	44	6
9HAZG80045	45	6
9HAZG80046	46	6

Some sizes may only be available in certain countries

DESCRIPTION

PVC compound reinforced with nitrile and polymer for professional protection against chemicals.
 Self-cleaning and non-slip SRA ++ outsole.
 Steel toe cap and sole. Thermal insulation: 0 ° C.
 Certified resistance against chemicals EN13832-3: 2006 J K O P Q R.

SECTORS

Extracting Oil and Gas

Heavy & process industries

Light Industries

Regional/public authorities

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Green
Color 2	Yellow
Weight	944 g
Upper	Acifort®
Toecap	Steel
Puncture resistant sole	Steel
Outsole	Acifort®
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol