

Ref. **9LAR120**

Indoor and dry environments

Low

Sandals

S1PS

0%
METAL

SR

FO



The +

- *Open shoe to be protected without suffering from heat.
- *Breathable upper and lining.
- *PU2D injected outsole: comfort and adherence.

PURCHASE PACKAGING

Ref.	Size	Carton
9LAR120038	38	6
9LAR120039	39	6
9LAR120040	40	6
9LAR120041	41	6
9LAR120042	42	6
9LAR120043	43	6
9LAR120044	44	6
9LAR120045	45	6
9LAR120046	46	6
9LAR120047	47	6

Some sizes may only be available in certain countries

DESCRIPTION

LARIMAR is a sandal with mesh and polyester upper which offer high breathability and comfort. Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. It is ideal for work dry environments.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Blue	Main assembly	Injected
Weight	558 g	Closing	Scratch closure
Upper	Suede leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/24/1803

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S1PS

Safety shoes

S1PS Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance