

Ref. **9QUAD**

Specialties

High

High shoes



The +

- *Easy-on and easy-off.
- *Welding sparks protective cover.
- *Midsole with front protective covering.
- *Footbridge supplying torsional rigidity.

PURCHASE PACKAGING

Ref.	Size	Carton
9QUAD36	36	
9QUAD38	38	10
9QUAD39	39	10
9QUAD40	40	10
9QUAD41	41	10
9QUAD42	42	10
9QUAD43	43	10
9QUAD44	44	10
9QUAD45	45	10
9QUAD46	46	10
9QUAD47	47	10

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
 Antipenetration textile sole
 External sole in double density PU/Rubber
 Upper in split leather
 Breathable mesh lining
 Padded Collar with PU
 Reinforcement: front in PU
 Kevlar seams

SECTORS

- Food-processing industry
- Regional/public authorities
- Construction - finishing work
- Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	717 g	Closing	Striped strap closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100332916**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)