

Ref. **9HOWL04**

Specialties

Low

Low shoes



S2



The +

- * Easy-on and easy-off.
- * Protective cover.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
9HOWL04035	35	6
9HOWL04036	36	6
9HOWL04037	37	6
9HOWL04038	38	6
9HOWL04039	39	6
9HOWL04040	40	6
9HOWL04041	41	6
9HOWL04042	42	6
9HOWL04043	43	6
9HOWL04044	44	6
9HOWL04045	45	6
9HOWL04046	46	6
9HOWL04047	47	6

Some sizes may only be available in certain countries



DESCRIPTION

HOWLITE safety shoe is a slip-on model in breathable microfiber, lined with a breathable mesh for optimal comfort of use throughout the day. This safety shoe guarantees the safety of the foot thanks to a metal toe cap at the front.

Equipped with a non-slip sole that absorbs energy through the heel, this model provides great stability to its wearer.

SECTORS

Food-processing industry

TECHNICAL FEATURES

Color	White	Main assembly	Injected
Color 2	Grey	Lining	Breathable 3D mesh
Weight	475 g		
Upper	Microfiber		
Toecap	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21006545

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S2

Safety shoes

S2 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Water penetration and absorption resistant upper

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol