

Ref. **9HEVL**

Indoor and dry environments

Low

Low shoes



S1P



0%
METAL

The +

- * Breathable upper and lining.
- * Flexibility and front reinforcement for easier kneeling at work.
- * Shock absorbing EVA midsole.

PURCHASE PACKAGING

Ref.	Size	Carton
9HEVL37	37	10
9HEVL38	38	10
9HEVL39	39	10
9HEVL40	40	10
9HEVL41	41	10
9HEVL42	42	10
9HEVL43	43	10
9HEVL44	44	10
9HEVL45	45	10
9HEVL46	46	10
9HEVL47	47	10

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax sole
External sole in double density EVA/Rubber
Reinforcement : front in rubber
Padded collar
Upper in Suede
Breathable mesh lining
Textile tightening loops

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Black	Insole	Removable, textile and foam
Color 2	Grey	Main assembly	Cemented
Weight	546 g	Reinforcement	Front
Upper	Suede leather / Mesh	location	
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0815

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)