

Ref. **9LEAH**

Indoor and dry environments

High

High shoes



### The +

- \*Compatible with ESD Protected Areas
- \*Comfort and lightweight
- \*Excellent grip

#### PURCHASE PACKAGING

Ref.	Size	Carton
9LEAH36	36	10
9LEAH37	37	10
9LEAH38	38	10
9LEAH39	39	10
9LEAH40	40	10
9LEAH41	41	10
9LEAH42	42	10
9LEAH43	43	10
9LEAH44	44	10
9LEAH45	45	10
9LEAH46	46	10
9LEAH47	47	10
9LEAH48	48	10

*Some sizes may only be available in certain countries*

See also

#### VARIANTS



9LEAL

#### DESCRIPTION

Composite toecap Antipenetration textile sole External sole in double density PU/PU Upper in Suede Additional pair of yellow laces delivered with the shoes Outsole resistant to hydrocarbons Antistatic outsole Energy absorbing heel Light and flexible

#### SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

#### APPLICATIONS

Painter,  
Electrician,  
Storekeeper, ...

## TECHNICAL FEATURES

Color	Grey	Outsole	PU
Color 2	Blue	Insole	Removable, textile and cushioned foam
Weight	591 g	Main assembly	Injected
Upper	Suede leather / Mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	PU		

## INSTRUCTION FOR USE AND STORAGE

**Instructi-ons for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructi-ons**

Place the shoes, when not in use, in a dry, clean and airy place. The tim einfluences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructi-ons**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/24/1213

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

EN ISO 20345:2022

Safety shoes

S1PS

**S1PS** Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value  $\geq$  950 N) - Non-metallic insert, 3.0mm diameter puncture needle

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance