

Ref. **9HYSA**

Synthetic Boots

PVC

Boots



SB



The +

- * Energy absorbing heel (E)
- * Fuel and oil resistant outsole (FO)

PURCHASE PACKAGING

Ref.	Size	Carton
9HYSA36	36	6
9HYSA37	37	6
9HYSA38	38	6
9HYSA39	39	6
9HYSA40	40	6
9HYSA41	41	6
9HYSA42	42	6
9HYSA43	43	6
9HYSA44	44	6
9HYSA45	45	6
9HYSA46	46	6
9HYSA47	47	6
9HYSA48	48	6

Some sizes may only be available in certain countries

DESCRIPTION

Steel toecap
External sole in green PVC
White PVC upper
White nylon lining

SECTORS

Heavy & process industries

Light Industries

Regional/public authorities

TECHNICAL FEATURES

Color	White
Color 2	Green
Weight	1 090 g
Upper	PVC
Toecap	Steel
Outsole	PVC nitrile
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **CE-1775-58/12**

Delivered by CTCP (1775) Rua de Fundões- Devesa Velha 3700 - 121 S. João da Madeira Portugal



EPI CAT. II

EN ISO 20345:2011

SB

SRA

Safety shoes

SB Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol