

Ref. **9HYDR**

Outdoor

High

High shoes



### The +

- \*Heel and toe scuff caps for a longer shoe's lifespan.
- \*Padded collar and bellows tongue for snug fit.
- \*Defined heel for better safety especially on ladders.

### PURCHASE PACKAGING

Ref.	Size	Carton
9HYDR38	38	10
9HYDR39	39	10
9HYDR40	40	10
9HYDR41	41	10
9HYDR42	42	10
9HYDR43	43	10
9HYDR44	44	10
9HYDR45	45	10
9HYDR46	46	10
9HYDR47	47	10
9HYDR48	48	

*Some sizes may only be available in certain countries*

### DESCRIPTION

Composite toecap  
Antipenetration textile sole  
External sole in double density PU/Rubber  
Upper in crazy horse leather  
Lining: Waterproof and Thinsulate membrane  
Reinforcement : front and back in TPU

### SECTORS

Mining  
Extracting Oil and Gas  
Energy (production and distribution)  
Infrastructure, building industry

### APPLICATIONS

Builder,  
Slater,  
Ramp agent,  
Luggage handler,  
Site supervisor,  
Dockers, ...

## TECHNICAL FEATURES

Color	Black	Insole	Removable, textile and cushioned foam
Color 2	Red		
Weight	778 g	Main assembly	Injected
Upper	Full grain leather	Reinforcement material	Anti-abrasion Stark®
Toecap	Composite	Reinforcement location	Heel / Front
Puncture resistant sole	Textile	Closing	Lacing closure
Midsole	PU	Lining	3M® Thinsulate® insulation
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB25011563

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

HI	Sole insulation against heat (30 minutes at 150°C)
HRO	Heat contact resistant outsole (60 seconds at 300°C)
CI	Shoe insulation against cold (30 minutes at -20°C)
EN ISO 20345:2022	Safety shoes
S7L	S7L Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance: - Sole puncture resistance (1100 Newton) - Non-metallic insert, 4.5mm diameter puncture needle- resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole - non-metallic insert type PL+ Water resistance of the entire shoe
SR	Resistance to slippage (ceramic floor + oil)
LG	Grip System - Unhooked heel
SC	Abrasion resistance of the toe-caps
FO	Hydrocarbons resistance

MAJ 06/10/2025