

Ref. **9OPAL**

Outdoor

Low

Low shoes



The +

- * Footbridge supplying torsional rigidity.
- * Heel scuff cap.
- * Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9OPAL38	38	10
9OPAL39	39	10
9OPAL40	40	10
9OPAL41	41	10
9OPAL42	42	10
9OPAL43	43	10
9OPAL44	44	10
9OPAL45	45	10
9OPAL46	46	10
9OPAL47	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



90PAH

DESCRIPTION

Breathable composite toecap
 Antipenetration textile sole
 External sole in double density PU/PU
 Upper in crazy horse leather
 Breathable mesh lining
 Reinforcement : front in PU and back in TPU

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

Color	Black	Outsole	PU
Color 2	Orange	Insole	Removable, textile and foam
Weight	605 g	Main assembly	Injected
Upper	Full grain leather	Closing	Lacing closure
Toecap	Composite	Lining	Moisture wicking non-woven membrane
Toecap 2	breathable	Defined heel	
Puncture resistant sole	Textile		
Midsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LEC F100341101

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

SRC

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol