

Ref. **9KYA150**

Indoor and dry environments

Low

Low shoes



S1P



0%  
METAL

### The +

- \*Breathable upper and lining.
- \*Non-magnetic.
- \*Wide range of sizes.
- \*Insole with silicone insert: comfort.

### PURCHASE PACKAGING

Ref.	Size	Carton
9KYA150036	36	6
9KYA150037	37	6
9KYA150038	38	6
9KYA150039	39	6
9KYA150040	40	6
9KYA150041	41	6
9KYA150042	42	6
9KYA150043	43	6
9KYA150044	44	6
9KYA150045	45	6
9KYA150046	46	6
9KYA150047	47	6
9KYA150048	48	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

KYANITE is a low shoe in micro-perforated suede leather with an moisture wicking non-woven lining.

This model has a composite toecap and an anti-perforation sole in textile for a better protection.

Its outsole is resistant to hydrocarbons and slipping on ceramic and metal floors.

The insole with silicone insert provides additional comfort.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Anthracite	Main assembly	Injected
Weight	525 g	Closing	Lacing closure
Upper	Suede leather	Lining	Moisture wicking non-woven membrane
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/20/3009EXT01/03/21

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol