

Ref. **9ONY180**

Indoor and dry environments

Low

Low shoes



The +

- * Ergonomic lacing system (breaking strength and abrasion tested by CTC France).
- * Breathability.
- * Outsole adherence.

PURCHASE PACKAGING

Ref.	Size	Carton
9ONY180038	38	6
9ONY180039	39	6
9ONY180040	40	6
9ONY180041	41	6
9ONY180042	42	6
9ONY180043	43	6
9ONY180044	44	6
9ONY180045	45	6
9ONY180046	46	6
9ONY180047	47	6

Some sizes may only be available in certain countries



DESCRIPTION

ONYX is an ESD safety shoe with a laceless tightening system. Its upper made of polyester mesh provides good breathability. Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. ONYX features a toe-cap and an anti-penetration plate made of composite for optimal protection.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Turquoise	Main assembly	Injected
Weight	548 g	Closing	Lacing closure
Upper	Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/11/20/2750EXT03/11/20

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)