

Ref. **9ONY180**

Indoor and dry environments

Low

Low shoes



### The +

- \* Ergonomic lacing system (breaking strength and abrasion tested by CTC France).
- \* Breathability.
- \* Outsole adherence.

### PURCHASE PACKAGING

Ref.	Size	Carton
9ONY180038	38	6
9ONY180039	39	6
9ONY180040	40	6
9ONY180041	41	6
9ONY180042	42	6
9ONY180043	43	6
9ONY180044	44	6
9ONY180045	45	6
9ONY180046	46	6
9ONY180047	47	6

*Some sizes may only be available in certain countries*



### DESCRIPTION

ONYX is an ESD safety shoe with a laceless tightening system. Its upper made of polyester mesh provides good breathability. Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. ONYX features a toe-cap and an anti-penetration plate made of composite for optimal protection.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Turquoise	Main assembly	Injected
Weight	548 g	Closing	Lacing closure
Upper	Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/11/20/2750EXT03/11/20

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)