

Ref. **9LAH052**

Specialties

High

High shoes

S3

SR

FO



The +

*Good resistance to hydrolysis, tested at CTC.

(special formulation of the midsole)

*Value for money.

PURCHASE PACKAGING

Ref.	Size	Carton
9LAH052038	38	10
9LAH052039	39	10
9LAH052040	40	10
9LAH052041	41	10
9LAH052042	42	10
9LAH052043	43	10
9LAH052044	44	10
9LAH052045	45	10
9LAH052046	46	10
9LAH052047	47	10

Some sizes may only be available in certain countries

DESCRIPTION

The LAZURITE S3 model is a high safety shoe. Its upper is made up of black and blue action leather. Its toe cap and plate are in steel. This model has a polyester lining and an EVA insole.

The collar and the tongue are padded for a snug fit. This shoe has 5 metal eyelets.

Its outsole in PU/rubber is anti-slip on steel floors and hydrocarbons resistant.

Thanks to the special formulation of its midsole, this shoe offers good resistance to hydrolysis

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Insole	Textile and foam, removable
Color 2	Blue	Main assembly	Injected
Weight	732 g	Closing	Lacing closure
Upper	Action leather	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/19/1563

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance