

Ref. **9PFSA**

Synthetic Boots

PVC

Boots



S5



The +

- * Waterproof.
- * Energy absorbing heel for better comfort.

PURCHASE PACKAGING

Ref.	Size	Carton
9PFSA37	37	6
9PFSA38	38	6
9PFSA39	39	6
9PFSA40	40	6
9PFSA41	41	6
9PFSA42	42	6
9PFSA43	43	6
9PFSA44	44	6
9PFSA45	45	6
9PFSA46	46	6
9PFSA47	47	6

Some sizes may only be available in certain countries

DESCRIPTION

Steel toecap
White polyester lining
Green PVC upper

SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	Green
Color 2	Black
Weight	1150 g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Steel
Outsole	PVC nitrile
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate CE-2790-161/2019

Delivered by ASSOCIAÇÃO PORTUGUESA DOS INDUSTRIAIS DO CALÇADO - COMPONENTES-ARTIGOS DE PELE E SEUS SUCEDÂNEOS (APPICAPS) (2790) RUA ALVES REDOL - 372 4050-040 PORTO - Portugal



EPI CAT. II

EN ISO 20345:2011

S5

SRA

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol