

Ref. **9MAN150**

Indoor and dry environments

Low

Low shoes



S1P



The +

- *Value for money.
- *Breathable upper and lining.
- *Wide range of sizes.
- *Insole with silicone insert: comfort.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|------------|------|--------|
| 9MAN150036 | 36 | 6 |
| 9MAN150037 | 37 | 6 |
| 9MAN150038 | 38 | 6 |
| 9MAN150039 | 39 | 6 |
| 9MAN150040 | 40 | 6 |
| 9MAN150041 | 41 | 6 |
| 9MAN150042 | 42 | 6 |
| 9MAN150043 | 43 | 6 |
| 9MAN150044 | 44 | 6 |
| 9MAN150045 | 45 | 6 |
| 9MAN150046 | 46 | 6 |
| 9MAN150047 | 47 | 6 |
| 9MAN150048 | 48 | 6 |

Some sizes may only be available in certain countries



DESCRIPTION

MANGANITE is a low shoe in micro-perforated suede leather with an moisture wicking non-woven lining.

This model has a steel toecap and an anti-perforation sole in steel for a better protection.

Its outsole is resistant to hydrocarbons and slipping on ceramic and metal floors.

The insole with silicone insert provides additional comfort.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

| | | | |
|-------------------------|---------------------------|---------------|-------------------------------------|
| Color | Anthracite | Main assembly | Injected |
| Weight | 571 g | Closing | Lacing closure |
| Upper | Suede leather | Lining | Moisture wicking non-woven membrane |
| Toecap | Steel | | |
| Puncture resistant sole | Steel | | |
| Midsole | PU | | |
| Outsole | PU | | |
| Insole | Removable, perforated EVA | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/20/3009

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

SRC

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol