

Ref. **9PROH10**

Multipurpose

High

High shoes



The +

- *Soft PU/PU outsole: cushioning and comfort.
- *Raised heel: stability on ladders.
- *Wide cleats and flex lines: optimized adaptability to the ground.
- *Nubuck upper with membrane: waterproof shoe.

PURCHASE PACKAGING

Ref.	Size	Carton
9PROH10035	35	6
9PROH10036	36	6
9PROH10037	37	6
9PROH10038	38	6
9PROH10039	39	6
9PROH10040	40	6
9PROH10041	41	6
9PROH10042	42	6
9PROH10043	43	6
9PROH10044	44	6
9PROH10045	45	6
9PROH10046	46	6
9PROH10047	47	6
9PROH10048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

CLAW PROOF is a lightweight, flexible and waterproof safety sneaker. With a membrane nubuck upper, CLAW PROOF ensures that the wearer's feet stay dry in wet weather. Its low density PU/PU outsole guarantees all day comfort. Its aluminum / composite protection system contributes to its sporty look.

SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Reinforcement	Front
Weight	683 g	location	
Upper	Nubuck leather	Lining	Breathable 3D mesh
Toecap	Aluminium	Defined heel	
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	PU Foam, removable		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/0722/1320 EXT 01/07/22

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

SRC

WR

ESD

COVERPERF - Damping



Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Water repellent shoe

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.