

Ref. **9MAN150**

Indoor and dry environments

Low

Low shoes



S1P



The +

- *Value for money.
- *Breathable upper and lining.
- *Wide range of sizes.
- *Insole with silicone insert: comfort.

PURCHASE PACKAGING

Ref.	Size	Carton
9MAN150036	36	6
9MAN150037	37	6
9MAN150038	38	6
9MAN150039	39	6
9MAN150040	40	6
9MAN150041	41	6
9MAN150042	42	6
9MAN150043	43	6
9MAN150044	44	6
9MAN150045	45	6
9MAN150046	46	6
9MAN150047	47	6
9MAN150048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

MANGANITE is a low shoe in micro-perforated suede leather with an moisture wicking non-woven lining.

This model has a steel toecap and an anti-perforation sole in steel for a better protection.

Its outsole is resistant to hydrocarbons and slipping on ceramic and metal floors.

The insole with silicone insert provides additional comfort.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Anthracite	Main assembly	Injected
Weight	571 g	Closing	Lacing closure
Upper	Suede leather	Lining	Moisture wicking non-woven membrane
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/20/3009

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol