

Ref. **9MARH**

Outdoor

High

High shoes



S3



The +

*Padded collar and bellows tongue for snug fit.

*Footbridge supplying torsional rigidity.

PURCHASE PACKAGING

Ref.	Size	Carton
9MARH38	38	10
9MARH39	39	10
9MARH40	40	10
9MARH41	41	10
9MARH42	42	10
9MARH43	43	10
9MARH44	44	10
9MARH45	45	10
9MARH46	46	10
9MARH47	47	10

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in double density PU/PU
 Upper in Nubuck
 Padded tongue and collar
 Non woven lining

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Brown	Main assembly	Injected
Weight	694 g	Reinforcement material	Anti-abrasion Stark®
Upper	Nubuck leather	Reinforcement location	Heel / Front
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Moisture wicking non-woven membrane
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100338957**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol