

Ref. **9PEAH**

Outdoor

High

High shoes



The +

- * Footbridge supplying torsional rigidity.
- * Heel scuff cap.
- * Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|---------|------|--------|
| 9PEAH38 | 38 | 10 |
| 9PEAH39 | 39 | 10 |
| 9PEAH40 | 40 | 10 |
| 9PEAH41 | 41 | 10 |
| 9PEAH42 | 42 | 10 |
| 9PEAH43 | 43 | 10 |
| 9PEAH44 | 44 | 10 |
| 9PEAH45 | 45 | 10 |
| 9PEAH46 | 46 | 10 |
| 9PEAH47 | 47 | 10 |

Some sizes may only be available in certain countries

See also

VARIANTS



9PEAL

DESCRIPTION

Composite toecap
 Antipenetration textile sole
 External sole in double density PU/PU
 Upper in crazy horse leather
 Breathable mesh lining
 Reinforcement : front in PU and back in TPU

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

| | | | |
|-------------------------|-------------------------------------|---------------|-----------------------------|
| Color | Black | Insole | Removable, textile and foam |
| Color 2 | Orange | Main assembly | Injected |
| Weight | 652 g | Closing | Lacing closure |
| Upper | Full grain leather / Polyamide mesh | Lining | Breathable 3D mesh |
| Toecap | Composite | Defined heel | |
| Puncture resistant sole | Textile | | |
| Midsole | PU | | |
| Outsole | PU | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LEC F100341101

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol