

Ref. **90PAH**

Outdoor

High

High shoes



The +

- * Footbridge supplying torsional rigidity.
- * Heel scuff cap.
- * Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
90PAH38	38	10
90PAH39	39	10
90PAH40	40	10
90PAH41	41	10
90PAH42	42	10
90PAH43	43	10
90PAH44	44	10
90PAH45	45	10
90PAH46	46	10
90PAH47	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



90PAL

DESCRIPTION

Breathable composite toecap
 Antipenetration textile sole
 External sole in double density PU/PU
 Upper in crazy horse leather
 Breathable mesh lining
 Reinforcement : front in PU and back in TPU

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Painter,
 Electrician,
 Storekeeper, ...

TECHNICAL FEATURES

Color	Black	Outsole	PU
Color 2	Orange	Insole	Removable, textile and foam
Weight	686 g	Main assembly	Injected
Upper	Full grain leather	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Toecap 2	breathable	Defined heel	
Puncture resistant sole	Textile		
Midsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/24/2216 Ext 02/09/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance