

Ref. **9MIL280**

Indoor and dry environments

Low

Low shoes



S1P

SR

FO



The +

- * Sporty style
- * Breathability
- * Front reinforcement
- * PU2D injected sole

PURCHASE PACKAGING

Ref.	Size	Carton
9MIL280038	38	10
9MIL280039	39	10
9MIL280040	40	10
9MIL280041	41	10
9MIL280042	42	10
9MIL280043	43	10
9MIL280044	44	10
9MIL280045	45	10
9MIL280046	46	10
9MIL280047	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



9MIL530



9MIL110

DESCRIPTION

MILERITE S1P is a low safety shoe inspired by sport design with mesh upper and lining which offer high breathability and comfort. The front reinforcement made of embossed leather is suitable for users working squatting or kneeling.

It ensures longer lifetime.

Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.

MILERITE features a toe-cap and an anti-penetration plate made of steel for optimal protection.

It is ideal for work dry environments.

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Blue	Insole	Removable, perforated EVA
Color 2	Green	Main assembly	Injected
Weight	580 g	Closing	Lacing closure
Upper	Mesh	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/19/2029 EXT 02/07/19

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance