

Ref. **90KEL**

Specialties

Low

Low shoes



The +

- * Easy-on and easy-off.
- * Protective cover.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
90KEL35	35	10
90KEL36	36	10
90KEL37	37	10
90KEL38	38	10
90KEL39	39	10
90KEL40	40	10
90KEL41	41	10
90KEL42	42	10
90KEL43	43	10
90KEL44	44	10
90KEL45	45	10
90KEL46	46	10
90KEL47	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



90KEC



90KEH

DESCRIPTION

The OKENITE safety shoe is a slip-on model in breathable PU microfiber, lined with a breathable mesh for optimal comfort of use throughout the day. This metal-free safety shoe guarantees the safety of the foot thanks to a composite toe cap at the front while maintaining its lightness. Equipped with a non-slip sole that absorbs energy through the heel, this model provides great stability to its wearer.

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Weight	427 g	Main assembly	Injected
Color	White	Lining	Breathable 3D mesh
Color 2	Grey		
Upper	Microfiber		
Toecap	Composite		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/06/23/0975

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S2

Safety shoes

S2 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Water penetration and absorption resistant upper

SR

Resistance to slippage (ceramic floor + oil)