

Ref. **9OPAL**

Outdoor

Low

Low shoes



### The +

- \* Footbridge supplying torsional rigidity.
- \* Heel scuff cap.
- \* Defined heel for better safety especially on ladders.

### PURCHASE PACKAGING

Ref.	Size	Carton
9OPAL38	38	10
9OPAL39	39	10
9OPAL40	40	10
9OPAL41	41	10
9OPAL42	42	10
9OPAL43	43	10
9OPAL44	44	10
9OPAL45	45	10
9OPAL46	46	10
9OPAL47	47	10

*Some sizes may only be available in certain countries*

See also

### VARIANTS



**90PAH**

### DESCRIPTION

Breathable composite toecap  
 Antipenetration textile sole  
 External sole in double density PU/PU  
 Upper in crazy horse leather  
 Breathable mesh lining  
 Reinforcement : front in PU and back in TPU

### SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

### APPLICATIONS

Builder,  
 Slater,  
 Ramp agent,  
 Luggage handler,  
 Site supervisor,  
 Docker, ...

## TECHNICAL FEATURES

Color	Black	Outsole	PU
Color 2	Orange	Insole	Removable, textile and foam
Weight	605 g	Main assembly	Injected
Upper	Full grain leather	Closing	Lacing closure
Toecap	Composite	Lining	Moisture wicking non-woven membrane
Toecap 2	breathable	Defined heel	
Puncture resistant sole	Textile		
Midsole	PU		

## INSTRUCTION FOR USE AND STORAGE

**Instructi-ons for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructi-ons**

Place the shoes, when not in use, in a dry, clean and airy place. The tim einfluences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructi-ons**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/24/2216 Ext 03/09/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

**S3S** Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance