coverguard®

TECHNICAL DATASHEET

EUROLITE SL505N

Ref.

1NISN

Handling and Precision Works

OIL TO SEE SECONTS C C C TINISNOS INISNOS EUROLITE SLSOSN



Oily Environment







The +

3/4 coating: increased skin protection against dermatitis risks
Excellent comfort
Exceptional grip in oily areas

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1NISN06	6	10	100
1NISN07	7	10	100
1NISN08	8	10	100
1NISN09	9	10	100
1NISN10	10	10	100
1NISN11	11	10	100

SALES PACKAGING

>1

Multiple

See also

DESCRIPTION

Black seamless support from polyester, 15 gauge,

Double coating in smooth orange nitrile on 3/4 and black nitrile sandy palm finish,

Knitted wrist

SECTORS

Heavy & process industries

Light Industries

Maintenance

Services and distribution

APPLICATIONS

Suitable for all fine work in oily and greasy environments, mechanical and automotive industry, machining of parts in the presence of cutting oil, handling of sheet metal, mechanical parts and sorting of small parts, maintenance work in wet environments, water, oils, greases, hydrocarbons, cutting work, stamping,

industrial maintenance and service work.

VARIANTS



1NIFB

TECHNICAL FEATURES



ColorBlackColor 2OrangeColor 3BlackShapeGloveGloves environmentOily

Glove type Seamless knitting
Support material Polyester, elastane

Coating level 3/4

Material of coating Nitrile

Coating finition Smooth

Coating level Palm

Material of coating Nitrile

Coating finition 2 Sandy

Type Of Cuff Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/01/23/0043

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

((

EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



Protection from mechanical risks