

Ref. **9RESH10**

Multipurpose

High

High shoes



### The +

- \*Soft PU/PU outsole: cushioning and comfort.
- \*Raised heel: stability on ladders.
- \*Wide cleats and flex lines: optimized adaptability to the ground.
- \*3D structured mesh upper: high abrasion resistance (laboratory tested).

### PURCHASE PACKAGING

| Ref.       | Size | Carton |
|------------|------|--------|
| 9RESH10035 | 35   | 6      |
| 9RESH10036 | 36   | 6      |
| 9RESH10037 | 37   | 6      |
| 9RESH10038 | 38   | 6      |
| 9RESH10039 | 39   | 6      |
| 9RESH10040 | 40   | 6      |
| 9RESH10041 | 41   | 6      |
| 9RESH10042 | 42   | 6      |
| 9RESH10043 | 43   | 6      |
| 9RESH10044 | 44   | 6      |
| 9RESH10045 | 45   | 6      |
| 9RESH10046 | 46   | 6      |
| 9RESH10047 | 47   | 6      |
| 9RESH10048 | 48   | 6      |

*Some sizes may only be available in certain countries*

### DESCRIPTION

CLAW RESIST is a lightweight, flexible and highly abrasion resistant safety sneaker.

This model has a resistant structured mesh upper, tested in a certified laboratory (CTC).

Its low density PU/PU outsole ensures all day comfort.

Its aluminum / composite protection system contributes to its sporty look.

### SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

|                         |            |                        |                                      |
|-------------------------|------------|------------------------|--------------------------------------|
| Color                   | Light blue | Insole                 | Foam, removable, with shock absorber |
| Color 2                 | Dark grey  | Reinforcement location | Front                                |
| Weight                  | 577 g      | Lining                 | Breathable 3D mesh                   |
| Upper                   | Mesh       | Defined heel           |                                      |
| Toecap                  | Aluminium  |                        |                                      |
| Puncture resistant sole | Textile    |                        |                                      |
| Midsole                 | PU         |                        |                                      |
| Outsole                 | PU         |                        |                                      |

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/22/1303 EXT 01/07/22

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.