

Ref. **9THSA**

Synthetic Boots

PVC

Waders



S5



### The +

\* Waterproof protection while working in the water.

#### PURCHASE PACKAGING

Ref.	Size	Carton
9THSA39	39	3
9THSA40	40	3
9THSA41	41	3
9THSA42	42	3
9THSA43	43	3
9THSA44	44	3
9THSA45	45	3
9THSA46	46	3
9THSA47	47	3

*Some sizes may only be available in certain countries*

#### DESCRIPTION

Steel toecap  
Steel antipenetration sole  
Green PVC upper  
Black PVC outsole  
White polyester lining

#### SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

## TECHNICAL FEATURES

Color	Green
Color 2	Black
Weight	1290 g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Stainless steel
Outsole	PVC nitrile
Lining	Polyester

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These Thigh Waders can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the Thigh Waders, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the Thigh Waders by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate CE-1775-54/12

Delivered by CTCP (1775) Rua de Fundões- Devesa Velha 3700 - 121 S. João da Madeira Portugal



EPI CAT. II

EN ISO 20345:2011

S5

SRA

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol