

Ref. 9SIBE

Outdoor

High

Boots



The +

- * Cold insulation.
- * Oustole resistant to -25°C.
- * Footbridge supplying torsional rigidity.

PURCHASE PACKAGING

Ref.	Size	Carton
9SIBE37	37	6
9SIBE38	38	6
9SIBE39	39	6
9SIBE40	40	6
9SIBE41	41	6
9SIBE42	42	6
9SIBE43	43	6
9SIBE44	44	6
9SIBE45	45	6
9SIBE46	46	6
9SIBE47	47	6

Some sizes may only be available in certain countries

DESCRIPTION

Steel toecap
 Antipenetration steel sole
 External sole in double density PU/PU
 Upper in full grain leather
 Fur interior

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	736 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Faux fur
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, faux fur and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/03/22/0428

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)