coverguard®

TECHNICAL DATASHEET

EUROCUT STRONG L440

Ref.

1CHLD00

Cut - General & Heavy Duty Work







Wet Environment











The +

Excellent grip in dry and wet area Chemical-free coating High visibility colours Thermal contact insulation 250°C / 15 sec

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CHLD00007	7	10	100
1CHLD00008	8	10	100
1CHLD00009	9	10	100
1CHLD00010	10	10	100
1CHLD00011	11	10	100

SALES PACKAGING

Hangable individual polybag

DESCRIPTION

Yellow seamless knit, 13 gauge, from HDPE, polyester, elastane, black smooth latex coating, embossed: diamond pattern. Knitted wrist.

SECTORS

Farming, silviculture and fishing

Energy (production and distribution)

Regional/public authorities

Infrastructure, building industry

Construction - finishing work

APPLICATIONS

Handling in dry or wet environments, with risk of cuts. Mechanical and automotive industries (handling of sheet metal, handling and sorting of small sharp parts), glass industry (handling of glass sheets), other industries (wet maintenance, green spaces, gardening, market gardening), maintenance work in wet environments, waste collection and handling.

TECHNICAL FEATURES

Gauge 13

Color Fluorescent yellow

Color 2 Black Shape Glove

Glove type Seamless knitting
Support material HPPE, nylon, spandex

Coating level Palm

Material of coating Latex

Coating finition Diamond

Type Of Cuff Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/11/21/1944

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

 ϵ

EPI CAT. II

EN ISO 21420:2020

EN ISO 21420:2020

EN388:2016

+ A1:2018



3.X.4.2.D.

ANSI



EN407:2020



LFI CAT. II

Protective gloves – General requirements and test methods

Protection from mechanical risks

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)

MAJ 13/08/2025