

Ref. **9RUBH**

Specialties

High

High shoes



The +

- * Breathable upper and lining.
- * Heel scuff cap.
- * Padding for snug fit.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
9RUBH36	36	10
9RUBH37	37	10
9RUBH38	38	10
9RUBH39	39	10
9RUBH40	40	10
9RUBH41	41	10
9RUBH42	42	10

Some sizes may only be available in certain countries

See also

VARIANTS



9RUBL

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax sole
External sole in Rubber
Plastic eyelets
Upper in Nubuck

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Insole	attached, textile and foam
Color 2	Grey	Main assembly	Injected
Weight	529 g	Reinforcement material	Anti-abrasion Stark®
Upper	Polyamide mesh / Nubuck leather	Reinforcement location	Heel
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	PU		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LEC F100332900

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)