

Ref. **9RELI**

Synthetic Boots

PU

Boots



HRO



PUROFORT



The +

- * Excellent grip in greasy environment.
- * Unique ankles support.
- * 50 % lighter.

PURCHASE PACKAGING

Ref.	Size	Carton
9RELI39	39	6
9RELI40	40	6
9RELI41	41	6
9RELI42	42	6
9RELI43	43	6
9RELI44	44	6
9RELI45	45	6
9RELI46	46	6
9RELI47	47	6

Some sizes may only be available in certain countries

DESCRIPTION

RELIANCE is a safety boot with a Purofort upper (50% lighter than rubber or traditional PVC boots). Antistatic Vibram XS Work outsole provides ultimate slip resistance and resistance on ceramic or steel floor. Defined heel insert anti-torsion allows unique ankles support. The boot is equipped with a steel toe cap, reflective trim at the top and puncture steel sole plate. The outsole resists to very high temperatures, up to 300°C in contact (for 1 minute) and its polyamide lining protects against cold down to -20°C.

SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	Dark grey
Weight	850 g
Upper	Purofort®
Toecap	Steel
Puncture resistant sole	Steel
Outsole	Purofort® Vibram
Insole	Polyurethane
Lining	Polyamide

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **BP 60112417 0001**

Delivered by TÜV (0197) Tillystraße 2 90431 Nürnberg Germany



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

CI

Shoe insulation against cold (30 minutes at -20°C)

CR

Cut resistant upper