

Ref. **9PYRO**

Outdoor

High

Boots



The +

- *Heel and toe Stark scuff caps.
- *Cushionned insole.
- *Footbridge supplying torsional rigidity.

PURCHASE PACKAGING

Ref.	Size	Carton
9PYRO37	37	5
9PYRO38	38	5
9PYRO39	39	5
9PYRO40	40	5
9PYRO41	41	5
9PYRO42	42	5
9PYRO43	43	5
9PYRO44	44	5
9PYRO45	45	5
9PYRO46	46	5
9PYRO47	47	5

Some sizes may only be available in certain countries

DESCRIPTION

Safety boot in full leather finished Pull up, water repellent Two side tabs on the upper so they can be pulled on easily. Dual density PU sole (wear layer = 1,1 and comfort layer = 0,65) with shock absorbing PU and reinforcement in the front for better protection. Non-metallic anti-perforation interlayer.

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and cushioned foam
Weight	724 g	Main assembly	Injected
Upper	Pull-up leather	Lining	Faux fur
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21006707

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)