

Ref. 9PUTP80

Synthetic Boots

PU

Boots



S5



CI



CR



PUROFORT

The +

- * Flexible and lightweight for use all day long.
- * Cold insulation.
- * Tear and wear resistant shaft.

PURCHASE PACKAGING

Ref.	Size	Carton
------	------	--------

Some sizes may only be available in certain countries

DESCRIPTION

The PUROFORT PRO model is a polyamide-lined, PU-coated PU safety boot. It is fitted with a removable Dunlop Comfort Insoles PRO series insole and a PU SRC outsole.

This boot has a protective toecap and a steel midsole against shock and penetration. The sole is insulated against the cold down to -20°C, allowing you to work even in cold environments.

SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	Green	Lining	Polyamide
Color 2	Black		
Weight	1,11Kg		
Upper	Purofort®		
Toecap	Steel		
Puncture resistant sole	Steel		
Outsole	Purofort®		
Insole	Polyurethane		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)



EN ISO 20345:2011

S5

SRC

CI

CR

EPI CAT. II

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Shoe insulation against cold (30 minutes at -20°C)

Cut resistant upper