coverguard®


TECHNICAL DATASHEET

SCHORL HIGH

Ref. 9SCHH10

Multipurpose

High









The +

- * Sport design
- * Metal free
- * Reflective trim
- * Defined and raised heel



PURCHASE PACKAGING

Ret.	Size	Carton
9SCHH10038	38	6
9SCHH10039	39	6
9SCHH10040	40	6
9SCHH10041	41	6
9SCHH10042	42	6
9SCHH10043	43	6
9SCHH10044	44	6
9SCHH10045	45	6
9SCHH10046	46	6
9SCHH10047	47	6

Some sizes may only be available in certain countries

See also

VARIANTS



9SCH100

DESCRIPTION

SCHORL is a high safety shoe inspired by the trail universe. Its upper made of Oxford polyester provides breathability and durabilty. The front, sides and back reinforcements in KPU increase long lastingness and is suitable to users working squatting or kneeling. Reflective stripes improve safety of people working at night. Metal free, this shoe features a composite toe-cap and a textile anti-penetration sole that bring better flexibility and better thermal insulation than steel shoes. The nitrile rubber clitted outsole and polyurethane midsole combine the advantages of both materials: comfort and resistance. SCHORL suits the requirements of standard indoor and outdoor uses.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

ColorBlackClosingLacing closureWeight702 gLiningBreathable 3D mesh

Upper Mesh
Toecap Composite
Puncture resistant Textile

sole

Midsole PU

Outsole Rubber nitrile

Insole Removable, perforated EVA

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/19/2786 EXT 01/06/20

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

 ϵ

EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

MAJ 09/11/2023