

Ref. **9PROH10**

Multipurpose

High

High shoes



FO



The +

- *Soft PU/PU outsole: cushioning and comfort.
- *Raised heel: stability on ladders.
- *Wide cleats and flex lines: optimized adaptability to the ground.
- *Nubuck upper with membrane: waterproof shoe.

PURCHASE PACKAGING

Ref.	Size	Carton
9PROH10035	35	6
9PROH10036	36	6
9PROH10037	37	6
9PROH10038	38	6
9PROH10039	39	6
9PROH10040	40	6
9PROH10041	41	6
9PROH10042	42	6
9PROH10043	43	6
9PROH10044	44	6
9PROH10045	45	6
9PROH10046	46	6
9PROH10047	47	6
9PROH10048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

CLAW PROOF is a lightweight, flexible and waterproof safety sneaker. With a membrane nubuck upper, CLAW PROOF ensures that the wearer's feet stay dry in wet weather. Its low density PU/PU outsole guarantees all day comfort. Its aluminum / composite protection system contributes to its sporty look.

SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Reinforcement location	Front
Weight	683 g	Lining	Breathable 3D mesh
Upper	Nubuck leather	Defined heel	
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	PU Foam, removable		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/10/24/2543 EXT 01/10/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

WR

Water repellent shoe

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S7S

Safety shoes

S7S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance: - Sole puncture resistance (1100 Newton) - Non-metallic insert, 3.0mm diameter puncture needle-resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole - non-metallic insert type PS+ Water resistance of the entire shoe

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance