

Ref. **9PIEM**

Outdoor

High

Boots



The +

- *Padded ankles for snug fit.
- *Heel scuff cap inserts.
- *Footbridge supplying torsional rigidity.

PURCHASE PACKAGING

Ref.	Size	Carton
9PIEM38	38	6
9PIEM39	39	6
9PIEM40	40	6
9PIEM41	41	6
9PIEM42	42	6
9PIEM43	43	6
9PIEM44	44	6
9PIEM45	45	6
9PIEM46	46	6
9PIEM47	47	6

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax sole
External sole in double density PU/PU
Fur interior
Upper in split leather
Malleolus reinforcement

SECTORS

Mining
Extracting Oil and Gas
Energy (production and distribution)
Infrastructure, building industry

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

TECHNICAL FEATURES

Color	Brown	Main assembly	Injected
Weight	798 g	Lining	Faux fur
Upper	Full grain leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB24015415

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)