

Ref. **9PUPO80**

Synthetic Boots

PU

Boots



S5



PUROFORT

### The +

- \* Flexible and lightweight for use all day long.
- \* Cold insulation.
- \* Tear and wear resistant shaft.

#### PURCHASE PACKAGING

Ref.	Size	Carton
9PUPO80035	35	6
9PUPO80036	36	6
9PUPO80037	37	6
9PUPO80038	38	6
9PUPO80039	39	6
9PUPO80040	40	6
9PUPO80041	41	6
9PUPO80042	42	6
9PUPO80043	43	6
9PUPO80044	44	6
9PUPO80045	45	6
9PUPO80046	46	6
9PUPO80047	47	6
9PUPO80048	48	6

*Some sizes may only be available in certain countries*

#### DESCRIPTION

The PUROFORT PRO model is a polyamide-lined, PU-coated PU safety boot. It has a removable Texon insole and a non-slip PU SRC outsole. This boot has a protective toecap and a steel midsole against shock and penetration. The sole is insulated against the cold down to -20°C, allowing you to work even in cold environments.

#### SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

## TECHNICAL FEATURES

Color	Green	Lining	Polyamide
Color 2	Black		
Weight	900 g		
Upper	Purofort®		
Toecap	Steel		
Puncture resistant sole	Steel		
Outsole	Purofort®		
Insole	Polyurethane		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **BP 60091395 0001**

Delivered by TÜV (0197) Tillystraße 2 90431 Nürnberg Germany



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

**S5** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)