

Ref. **9RFPO90**

Synthetic Boots

PU

Boots



The +

- * Fur lined for cold insulation.
- * Lightweight and flexible for use all day long.
- * Tear and wear resistant shaft.

PURCHASE PACKAGING

Ref.	Size	Carton
9RFPO90037	37	6
9RFPO90038	38	6
9RFPO90039	39	6
9RFPO90040	40	6
9RFPO90041	41	6
9RFPO90042	42	6
9RFPO90043	43	6
9RFPO90044	44	6
9RFPO90045	45	6
9RFPO90046	46	6
9RFPO90047	47	6
9RFPO90048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

Steel toecap
 Steel antipenetration sole
 External sole in Brown PU, cold insulating
 Upper in brown PU
 Fur polyamide lining
 Texon insole
 Upper height: 28,5 cm

Caution / Small size: Allow a gap of 2 sizes

SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	Brown	Lining	Polyamide
Color 2	Black		
Weight	850 g		
Upper	Purofort®		
Toecap	Steel		
Puncture resistant sole	Steel		
Outsole	Purofort®		
Insole	Polyurethane		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **BP 60091395 0001**

Delivered by TÜV (0197) Tillystraße 2 90431 Nürnberg Germany



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)