

Ref. **9RESL10**

Multipurpose

Low

Low shoes



The +

- *Soft PU/PU outsole: cushioning and comfort.
- *Raised heel: stability on ladders.
- *Wide cleats and flex lines: optimized adaptability to the ground.
- *3D structured mesh upper: high abrasion resistance (laboratory tested).

PURCHASE PACKAGING

Ref.	Size	Carton
9RESL10035	35	6
9RESL10036	36	6
9RESL10037	37	6
9RESL10038	38	6
9RESL10039	39	6
9RESL10040	40	6
9RESL10041	41	6
9RESL10042	42	6
9RESL10043	43	6
9RESL10044	44	6
9RESL10045	45	6
9RESL10046	46	6
9RESL10047	47	6
9RESL10048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

CLAW RESIST is a lightweight, flexible and highly abrasion resistant safety sneaker.

This model has a resistant structured mesh upper, tested in a certified laboratory (CTC).

Its low density PU/PU outsole ensures all day comfort.

Its aluminum / composite protection system contributes to its sporty look.

SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Light blue	Insole	PU Foam, removable, with shock absorber
Color 2	Dark grey	Reinforce-ment location	Front
Weight	566 g	Lining	Breathable 3D mesh
Upper	Mesh	Defined heel	
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructi-ons for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The tim einfluences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/24/2251

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

CI

Shoe insulation against cold (30 minutes at -20°C)

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

SC

Abrasion resistance of the toe-caps

FO

Hydrocarbons resistance

MAJ 30/09/2024