

Ref. **9PUMG**

Synthetic Boots

PU

Boots



S4



PUROFORT

The +

- * Women fit (size 4 to 6.5).
- * Flexible and lightweight for use all day long.
- * Ergonomic sole for excellent foot support

PURCHASE PACKAGING

Ref.	Size	Carton
9PUMG37	37	6
9PUMG38	38	6
9PUMG39	39	6
9PUMG40	40	6
9PUMG41	41	6
9PUMG42	42	6
9PUMG43	43	6
9PUMG44	44	6
9PUMG45	45	6
9PUMG46	46	6
9PUMG47	47	6

Some sizes may only be available in certain countries

DESCRIPTION

The PUROFORT SAFETY model is a safety boot in PU lined with polyamide coated PU. It has a removable Texon insole and a non-slip PU outsole for ceramic floors.

This boot has a protective toecap and a steel midsole against shock and penetration. Its sole is insulated against the cold down to -20°C , allowing you to work even in cold environments.

SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	White
Color 2	Blue
Weight	800 g
Upper	Purofort®
Toecap	Steel
Outsole	PU
Insole	Polyurethane
Lining	Polyamide

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate BP60091395 0001

Delivered by TÜV (0197) Tillystraße 2 90431 Nürnberg Germany



EPI CAT. II

EN ISO 20345:2011

S4

SRC

CI

Safety shoes

S4 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Shoe insulation against cold (30 minutes at -20°C)