

Ref. 1NIST00

Handling and Precision Works

Dry Environment



The +

COVERPERF BREATHABILITY: Comfort, maximum breathability
COVERPERF DURABILITY: Ultra high abrasion resistance
 Excellent grip
 Adaptative shape after 3-5 minutes

PURCHASE PACKAGING

| Ref. | Size | Inner | Carton |
|------------|------|-------|--------|
| 1NIST00007 | 7 | 10 | 100 |
| 1NIST00008 | 8 | 10 | 100 |
| 1NIST00009 | 9 | 10 | 100 |
| 1NIST00010 | 10 | 10 | 100 |
| 1NIST00011 | 11 | 10 | 100 |

SALES PACKAGING

Hangable individual polybag

DESCRIPTION

EUROLITE MAX25 gloves, grey polyamide seamless knit, 15 gauge, palm coating in black sandy nitrile.

Knitted wrist,

Certified OEKO-TEX® STANDARD 100, CQ 1301/1, IFTH or SH020 131830, TESTEX

SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Maintenance

Construction - finishing work

APPLICATIONS

Precision work in dry or slightly oily environments suitable for prolonged use without heating the hand. Fine handling in the presence of abrasive materials: industry (assembly line), metal manufacturing (precision mechanics, assembly station), logistics (order preparation, reception of goods), construction trades (door frames, handling, etc.)

TECHNICAL FEATURES



Gauge 15

| | |
|---------------------|----------------------|
| Color | Dark grey |
| Color 2 | Black |
| Shape | Glove |
| Gloves environment | Dry environment |
| Glove type | Seamless knitting |
| Support material | Polyamide / elastane |
| Coating level | Palm |
| Material of coating | Nitrile |
| Coating finition | Sandy |
| Type Of Cuff | Elastic wrist |

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/06/21/1080

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.1.3.1.X.

COVERPERF - Durability/Abrasion resistance

Gloves tested in a certified laboratory (CTC) offering excellent resistance to abrasion. Resistance above 20 000 cycles, compared to 8000 cycles for standard EN 388



COVERPERF - Breathability

Gloves tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 60mg/cm2/8h

