

Ref. **9SAND20**

Outdoor

High

High shoes



### The +

- \*EVA/nitrile rubber outsole: flexible and resistant for long-lasting wear.
- \*Oxford fabric cut-out at the ankle: optimized flexibility.
- \*Anti-abrasion protection at the back: safety.

### PURCHASE PACKAGING

Ref.	Size	Carton
9SAND20036	36	6
9SAND20037	37	6
9SAND20038	38	6
9SAND20039	39	6
9SAND20040	40	6
9SAND20041	41	6
9SAND20042	42	6
9SAND20043	43	6
9SAND20044	44	6
9SAND20045	45	6
9SAND20046	46	6
9SAND20047	47	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

The SAND model combines comfort and solidity. Recommended for all outdoor work, it is equipped with a waterproof upper. Its EVA midsole and nitrile rubber outsole provide stability and support for the user. This model is equipped with a composite / textile protection.

### SECTORS

Mechanicals constructions

Regional/public authorities

Maintenance

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

## TECHNICAL FEATURES

Color	Beige	Lining	Breathable 3D mesh
Weight	572 g		
Upper	Nubuck leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		
Closing	Lacing closure		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/06/22/1092

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.