

Ref. **9RUBL**

Specialties

Low

Low shoes



### The +

- \* Breathable upper and lining.
- \* Heel scuff cap.
- \* Padding for snug fit.
- \* Rounded heel for more comfortable driving.

### PURCHASE PACKAGING

Ref.	Size	Carton
9RUBL36	36	10
9RUBL37	37	10
9RUBL38	38	10
9RUBL39	39	10
9RUBL40	40	10
9RUBL41	41	10
9RUBL42	42	10

*Some sizes may only be available in certain countries*

See also

### VARIANTS



9RUBH

### DESCRIPTION

Composite toecap  
Antipenetration textile Wellmax sole  
External sole in Rubber  
Plastic eyelets  
Upper in Nubuck

### SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

## TECHNICAL FEATURES

Color	Black	Insole	Attached, textile and foam
Color 2	Grey	Main assembly	Injected
Weight	483 g	Reinforcement material	Anti-abrasion Stark®
Upper	Polyamide mesh / Nubuck leather	Reinforcement location	Heel
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	PU		
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LEC F100332900

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)