

Ref. **9SIH150**

Multipurpose

High

High shoes



S3



The +

- \*Breathable and water repellent upper.
- \*Reflective stripe with multiple faces.
- \*Heel and toe scuff cap.

### PURCHASE PACKAGING

Ref.	Size	Carton
9SIH150037	37	6
9SIH150038	38	6
9SIH150039	39	6
9SIH150040	40	6
9SIH150041	41	6
9SIH150042	42	6
9SIH150043	43	6
9SIH150044	44	6
9SIH150045	45	6
9SIH150046	46	6
9SIH150047	47	6

*Some sizes may only be available in certain countries*

See also

### VARIANTS



**9SIL150**

### DESCRIPTION

SILVER is a waterproof shoe, in suede and nylon. The breathability of the materials that make up this model make it a safety shoe with comfortable use and long-lasting performance. Equipped with a steel toe cap and midsole, it also features a dual density PU outsole. The shoe is designed to resist slipping on steel and ceramic floors

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Anthracite	Main assembly	Injected
Weight	669 g	Closing	Lacing closure
Upper	Suede leather / Polyamide mesh	Lining	Moisture wicking non-woven membrane
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Textile and foam, removable		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/23/1342 EXT 01/08/23

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)