

Ref. **9SCH100**

Multipurpose

Low

Low shoes

S3



0%  
METAL



The +

- \* Sport design
- \* Metal free
- \* Reflective trim
- \* Defined and raised heel

### PURCHASE PACKAGING

Ref.	Size	Carton
9SCH100038	38	10
9SCH100039	39	10
9SCH100040	40	10
9SCH100041	41	10
9SCH100042	42	10
9SCH100043	43	10
9SCH100044	44	10
9SCH100045	45	10
9SCH100046	46	10
9SCH100047	47	10

*Some sizes may only be available in certain countries*

See also

### VARIANTS



9SCHH10

### DESCRIPTION

SCHORL is a low safety shoe inspired by the trail universe. Its upper made of Oxford polyester provides breathability and durability. The front, sides and back reinforcements in KPU increase long lastingness and is suitable to users working squatting or kneeling. Reflective stripes improve safety of people working at night. Metal free, this shoe features a composite toe-cap and a textile anti-penetration sole that bring better flexibility and better thermal insulation than steel shoes. The nitrile rubber clitted outsole and polyurethane midsole combine the advantages of both materials: comfort and resistance. SCHORL suits the requirements of standard indoor and outdoor uses.

### SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

### APPLICATIONS

Luggage handler,  
Delivery driver, ...

## TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	670 g	Closing	Lacing closure
Upper	Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/19/2786

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol