

Specialties

High

High shoes



S3



The +

- * Welding sparks protective cover.
- * Defined heel for better safety especially on ladders.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|------------|------|--------|
| 9QUAR10039 | 39 | 6 |
| 9QUAR10040 | 40 | 6 |
| 9QUAR10041 | 41 | 6 |
| 9QUAR10042 | 42 | 6 |
| 9QUAR10043 | 43 | 6 |
| 9QUAR10044 | 44 | 6 |
| 9QUAR10045 | 45 | 6 |
| 9QUAR10046 | 46 | 6 |

Some sizes may only be available in certain countries



DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in double density PU/PU
 Upper in split leather
 Breathable non woven Tybrelle lining
 BelLow shoess Tongue : inside PU, outside buffalo leather
 Padded Collar with PU

SECTORS

Construction - finishing work

TECHNICAL FEATURES

| | | | |
|--------------------------------|--------------------|----------------------|-------------------------------------|
| Color | Black | Insole | Removable, textile and foam |
| Color 2 | Black | Main assembly | Injected |
| Weight | 622 g | Closing | Striped strap closure |
| Upper | Full grain leather | Lining | Moisture wicking non-woven membrane |
| Toecap | Composite | | |
| Puncture resistant sole | Textile | Defined heel | |
| Midsole | PU | | |
| Outsole | PU | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/06/22/1160

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol